



# **ISOLATE<sup>2</sup>**

Fire Retardant GRP Door System

MOBILITY THRESHOLD



WHEELCHAIR THRESHOLD Isolate<sup>2</sup> is a 30 minute fire door with a distinctive grain definition finish and greater thermal efficiency with improved u values. It is available in five styles and a range of door leaf colour options in a white uPVC frame. Isolate<sup>2</sup> features a 44mm door leaf made up of two 2mm GRP skins with a phenolic foam core set into a 64mm white uPVC frame and is tested to BS EN 942. It is low maintenance and features a multi-point, high security Winkhaus AV2 locking mechanism with lever handle and stainless steel hinges.

Isolate<sup>2</sup> is available in three double glazed styles with a choice of Georgian wire (GW) in clear or obscure finishes, or a choice of Pyroguard (PY) clear or satin.

An overhead door closer is supplied as standard.

Sidelights and toplights are available with Isolate<sup>2</sup> fire doors. Double sidelights are

not available. Sidelights and toplights cannot be supplied fully welded. Sidelights can only be supplied with midrails.

#### **DIMENSIONS**

#### **Fire Door + Frame**

784mm - 1006mm 1980mm - 2080mm

	Double Glazed	Outside Pane	Spacer	Argon Gas	Inside Pane
Option 1	✓	Georgian Wire Clear (GW)	Stainless Steel	✓	Laminated + Low E
Option 2	1	Georgian Wire Obscure (GW)	Stainless Steel	✓	Laminated + Low E
Option 3	✓	Pyroguard Clear (PY)	Stainless Steel	✓	Toughened + Low E
Option 4	1	Pyroguard Clear (PY)	Stainless Steel	✓	Toughened Only Satin









### **Solid Fire Door Styles**







FDM1

## **Colour Options Available**











## **Glazed Fire Door Styles**







FDG3



FDM2

